

13281 U.S. PTO  
020404

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24

**RECOVERY FORCE ADJUSTMENT DEVICE**  
**FOR A PADDLE OF A CYMBAL STAND**

**BACKGROUND OF THE INVENTION**

**1. Field of the Invention**

The present invention relates to a recovery force adjustment device, and more particularly to a recovery force adjustment device for a paddle of a cymbal stand so that the user is able to easily adjust the magnitude of the paddle recovery force to adapt to different performers with different habits

**2. Description of Related Art**

With reference to Fig. 7, a conventional adjusting device for changing the magnitude of the recovery force from the transmission rod (50) to the paddle (60) of a cymbal stand (70) includes a bonding block (53) securely connecting the first rod (51) to the second rod (52) of the transmission rod (50), a stop (54) formed on a mediate portion of the first rod (51) and having a disk (56) extending from the stop (54) and a recovery spring (55) mounted around the first rod (51) and sandwiched between the disk (56) and the bonding block (53). A sleeve (57) is screwingly connected to the outer periphery of the cymbal stand (70) and having an indentation (not numbered) defined to receive therein the disk (56).

When the recovery force of the recovery spring (55) is required to change, the user is able to rotate the sleeve (57) to change the distance between the disk (56) and the bonding block (53). When the distance between the disk (56) and the bonding block (53) is changed, the extension length of the recovery spring (55) is also changed. Therefore, the force required to move the paddle (60) downward relative to the cymbal stand (70) is changed.

1           This adjustment of the recovery force requires the user to continuously  
2 rotate the sleeve (57) until the required recovery force magnitude is reached.  
3 That is, the adjustment process of the magnitude of the recovery force is  
4 troublesome and inefficient.

5           To overcome the shortcomings, the present invention tends to provide an  
6 improved recovery- force adjusting device for a paddle of a cymbal stand to  
7 mitigate the aforementioned problems.

#### 8 SUMMARY OF THE INVENTION

9           The primary objective of the present invention is to provide an improved  
10 recovery force- adjusting device to allow the user to easily adjust the magnitude  
11 of the recovery force from the recovery spring to the paddle of the cymbal stand.

12           Another objective of the present invention is to provide a handle  
13 pivotally mounted on the supporting seat of the cymbal stand, a driving ring  
14 movably mounted around a column of the cymbal stand and extending through  
15 the column and a rotating sleeve rotatably mounted around the column. The  
16 driving ring has two extensions oppositely extending toward the rotating sleeve  
17 which has a set of first teeth formed on a bottom portion of an outer periphery of  
18 the rotating sleeve, a set of second teeth and a set of third teeth formed on the  
19 outer periphery of the rotating sleeve, wherein both the second set of teeth and  
20 the third set of teeth are inclined with respect to the first set of teeth and  
21 oppositely correspond to each other. The supporting seat has a wedge formed on  
22 an inner face of the supporting seat to correspond to a tooth of the first set of  
23 teeth of the rotating sleeve. Therefore, when the two extensions are positioned in  
24 teeth of both the second and third sets of teeth, the wedge is on a slope of a tooth

1 of the first set of teeth and when the handle is pivoted to force the wedge to be  
2 positioned in the tooth of the first set of teeth, the sliding movement of the wedge  
3 along the slope of the tooth of the first set of teeth forces the rotating sleeve to  
4 rotate, which allows the two extensions to correspond to and be received in  
5 different two teeth respectively of the second set of teeth and the third set of teeth.  
6 Thus the recovery force from the recovery spring is changed.

7 Other objects, advantages and novel features of the invention will  
8 become more apparent from the following detailed description when taken in  
9 conjunction with the accompanying drawings.

#### 10 BRIEF DESCRIPTION OF THE DRAWINGS

11 Fig. 1 is a perspective view of the cymbal stand with the recovery force  
12 adjusting device of the present invention;

13 Fig. 2 is a side plan view showing the recovery force adjusting device of  
14 the present invention;

15 Figs. 3 and 4 are schematic side plan views in partial section, wherein  
16 when the wedge is on a slope of a tooth of the first set of teeth, the two extensions  
17 are located in teeth of the second and the third sets of teeth;

18 Figs. 5 and 6 are schematic side plan views in partial section showing  
19 that when the handle is pivoted to drive the driving ring upward relative to the  
20 supporting ring, the wedge is received in a corresponding tooth of the first set of  
21 teeth; and

22 Fig. 7 is a schematic cross sectional view of a conventional recovery  
23 force adjusting device for a cymbal stand.

#### 24 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

1           With reference to Fig. 1, a cymbal stand (10) has a paddle (20) movably  
2   connected to the cymbal stand (10) via a transmission rod (11) in a column (not  
3   numbered) such that a cymbal (not shown) on top of the transmission rod (11) is  
4   driven by the movement of the paddle (20). It is to be appreciated that the  
5   mechanism for the transmission rod (11) to resume its original position after  
6   movement of the paddle (20) is the spring (as shown in Fig. 3) which is mounted  
7   around the transmission rod (11). The spring has a first distal end securely  
8   connected to the paddle (20) and a second distal end securely connected to a stop  
9   movably received in the column and mounted outside the transmission rod (11).  
10   Because the recovery mechanism of the cymbal stand (10) is conventional in the  
11   art, detailed description of the interaction of the paddle (20) and the recovery  
12   spring, as well as the stop is omitted for brevity.

13           With reference to Figs. 2 and 3, the recovery force adjusting device in  
14   accordance with the present invention has a supporting seat (40) securely  
15   mounted outside the column (100) of the cymbal stand (10) and has a cutout (400)  
16   defined in the supporting seat (40) to receive therein a driving ring (30). The  
17   driving ring (30) has a pin (14), and two extensions (31) oppositely extending  
18   downward. The pin (14) extends through the driving ring (30) and the column  
19   (100) as well as the stop inside the column (100) and is moved along a slot (13)  
20   defined in the column (100). A rotating sleeve (50A) is rotatably sandwiched  
21   between the driving ring (30) and the supporting seat (40). The rotating sleeve  
22   (50A) has a first set of teeth (51A) formed on an outside bottom portion of the  
23   rotating sleeve (50A), a second set of teeth (52A) and a third set of teeth (53A) to  
24   correspond to the two extensions (31) of the driving ring (30). Both the second

1 set of teeth (52A) and the third set of teeth (53A) are formed on an outer  
2 periphery of the rotating sleeve (50A) and inclined relative to the first set of teeth  
3 (51A) and opposite to one another. That is, the first set of teeth (51A) is linearly  
4 formed on the outer periphery of the rotating sleeve (50A) and horizontal to the  
5 radius of the rotating sleeve (50A). However, the second and third sets of teeth  
6 (52A,53A) are formed in a descending manner such that both the second set of  
7 teeth (52A) and the third set of teeth (53A) are inclined relative to the first set of  
8 teeth (51A).

9 With reference to Figs. 4 and 5, the supporting seat (40) has a wedge (43)  
10 formed on an inner periphery of the supporting seat (40) to correspond to a tooth  
11 of the first set of teeth (51A). A recovery spring (36) is provided between the  
12 supporting seat (40) and the rotating sleeve (50A). Furthermore, a handle (42) is  
13 pivotally connected to the supporting seat (40) and the pin (14) extends through  
14 both sides of the handle (42). Thus pivotal movement of the handle (42) is able to  
15 drive the driving ring (30) to move up and down relative to the column (100).

16 It is to be noted that when the two extensions (31) are received in  
17 corresponding teeth in the second and the third sets of teeth (52A,53A)  
18 respectively, the wedge (43) corresponds to a slope of the first set of teeth (51A).  
19 When the two extensions (31) are away from the corresponding teeth of the  
20 respective second and third sets of teeth (52A,53A), the release of the recoil  
21 force from the recovery spring (36) forces the rotating sleeve (50A) to move  
22 upward, which allows the wedge (43) to be received in a corresponding tooth of  
23 the first set of teeth (51A). Before the wedge (43) is received in a corresponding  
24 tooth of the first set of teeth (51A), the wedge (43) aligns with a slope of the

1 corresponding tooth of the first set of teeth (51A). Therefore, after the wedge (43)  
2 is received in the corresponding tooth of the first set of teeth (51A) due to the  
3 upward movement of the handle (42) to drive the driving ring (30) to move  
4 upward accordingly, the rotation of the rotating sleeve (50A) makes a slope of  
5 the respective tooth of the second set of teeth (52A) and the third set of teeth  
6 (53A) to align with the extensions (31). When the handle (42) and the driving  
7 ring (30) are lowered, the rotating sleeve (50A) is also lowered due to the  
8 abutment of the two extensions (31) to bottom faces of the corresponding teeth  
9 of the second and third sets of teeth (52A,53A). Sliding movement of the two  
10 extensions (31) on the slopes of the corresponding teeth of the second set of teeth  
11 (52A) and the third set of teeth (53A) causes the wedge (43) to misalign with a  
12 tooth of the first set of teeth (51A). After the two extensions (31) are received in  
13 the corresponding teeth of the second and third sets of teeth (52A,53A), the  
14 interaction between the driving ring (30) and the rotating sleeve (50A) resumes  
15 the original relationship as previously described.

16 Therefore, the up-and-down movement of the rotating ring (30) due to  
17 the pivotal movement of the handle (42) is able to drive the rotating sleeve (50A)  
18 to rotate clockwise or counterclockwise depending on which of the slopes of the  
19 first set of teeth (51A) the wedge (43) aligns with. Further, because the second  
20 set of teeth (52A) and the third set of teeth (53A) are inclined relative to the first  
21 set of teeth (51A), the rotation of the rotating sleeve (50A) allows the two  
22 extensions (31) to be received in different teeth of the second set of teeth (52A)  
23 and the third set of teeth (53A) respectively. Therefore, the downward force of  
24 the rotating sleeve (50A) to the recovery spring (36) is variable, which also

1 means that the position of the driving ring (30) is changeable and thus the  
2 extension of the spring inside the column (100) and around the transmission rod  
3 (11) is also changeable. The purpose of changing the recovery force to the paddle  
4 (20) is thus accomplished.

5 With the recovery force adjusting device of the present invention, the  
6 user is able to adjust the recovery force of the spring to the paddle by pivoting the  
7 handle (42) to achieve the purpose of changing the position of the driving ring  
8 (30). Thus after the position of the driving ring (30) is changed, the compression  
9 to the spring is changed and the force required to pivot the paddle (20) is also  
10 changed.

11 It is to be understood, however, that even though numerous  
12 characteristics and advantages of the present invention have been set forth in the  
13 foregoing description, together with details of the structure and function of the  
14 invention, the disclosure is illustrative only, and changes may be made in detail,  
15 especially in matters of shape, size, and arrangement of parts within the  
16 principles of the invention to the full extent indicated by the broad general  
17 meaning of the terms in which the appended claims are expressed.